



## MULTI-CHARGE DOCK A920 POINT OF SALE BATTERY CHARGER

Part Number 404296-2001

Designed and manufactured for UK based payment solutions provider Secure Retail Ltd., the Multi-Charge Dock A920 is a charger designed to simultaneously charge up to twenty PAX A920 point of sale terminal batteries. Charging is by direct connection of the batteries to the charger.

The simple, compact design is both desk or wall mountable. The charger is ideally suited to modern 24 hour hospitality and retail environments where payment terminals are in continuous operation. The charger eliminates the downtime experienced when PAX A920 batteries are charged individually whilst still in their device.

A charging status indicator on every channel provides an intuitive user interface and allows easy identification of fully charged batteries and general charging progress. Operation is fully automatic - simply insert a battery and the charging will be carried out without further user input.

The charger is powered from a universal AC mains supply, catering for global use. The fanless operation ensures long service life with minimal user maintenance. The charger includes all the required electronic features to ensure safe and efficient battery charging whilst promoting long battery service life.



## TECHNICAL DATA:

AC Input	
Connector AC IN	85 - 264V AC, 50/60Hz, 2.5A Max, 150W Max
Input Connector	IEC 60320 C14 type. (Mains supply cables can be supplied to customer's requirements).
Charging Output	
Battery Charging Output	Twenty Independent Channels to suit Icon Energy Systems IS900 Batteries. 4.2V, 1Amp current limit per channel.
Environmental	
Operating Temperature	0°C to +40°C
Storage Temperature	-20°C to +70°C
Operating Environment	Sheltered environment, flat surface or wall mounted, free air. IP20
Mechanical	
Dimensions	348mm(w) X 538mm(d) X 66mm(h)
Weight	3.2kg (charger only)